IN THE CLAIMS

The claims of the present application as set forth below marked with changes.

Claims 1 - 19 (Cancelled)

20.(Currently Amended) A method for output of data from a computer system to an output device, comprising the steps of:

generating a master document having a variable data area and having a static data area; marking said variable data area;

inserting variable data into said variable data area to provide a serial data stream with individual documents, said individual documents respectively containing both variable data as well as static data;

separating said variable data of said serial data stream from said static data on a basis of said marking;

transmitting said variable data separated from said static data from a first individual document to the output device;

storing said static data of said first individual document in said output device;

said static data of following individual documents are not transmitted to said output device; and

joining said variable data in turn with the stored static data individual document by individual document in said output device;

said marking step of said variable data area ensues by a visually perceptible identification, said visually perceptible identification is a chromatic marking that appears on the printed document in the same color as the static data when printed.

21.(Previously Presented) A method as claimed in claim 20, wherein said output device is a printer device.

Claims 22 and 23 (Cancelled)

24.(Currently Amended) A method as claimed in claim 20 elaim 22, wherein said output device is a printer device, and said marking ensues with a color that lies outside a printable color spectrum of said printer device so that the variable data is not printed in said color of said chromatic marking but is printed in a same color as the color of the static data.

- 25.(Previously Presented) A method as claimed in claims 20, further comprising the step of: indicating a scope of said master document.
- 26.(Previously Presented) A method as claimed in claim 20, further comprising the step of: transmitting characteristic data to said output device with said variable data.
- 27.(Previously Presented) A method as claimed in claim 25, wherein said characteristic data includes at least one of: position data, font data and color data.
- 28.(Previously Presented) A method as claimed in claim 20, further comprising the step of: storing said static data in a macro datafile.
- 29.(Previously Presented) A method as claimed in claim 20, further comprising the step of: generating said serial data stream in one of the printer languages PCL, PostScript and LCDS.
- 30.(Previously Presented) A method as claimed in claim 20, wherein one of said master document and a second document is a document of printer language IPDS.
- 31.(Previously Presented) A method as claimed in claim 30, wherein said document of printer language IPDS is one of an overlay and a page segment.
- 32.(Previously Presented) A method as claimed in claim 20, wherein one of said master document and said second document is a document of print data language LCDS.
- 33.(Previously Presented) A method as claimed in claim 20, further comprising the step of:
 controlling said data output in one of a Windows system environment and a windows-like system environment via data that are input via a user interface.
- 34.(Previously Presented) A method as claimed in claim 20, further comprising the steps of: generating said master document;

linking at least one second document logically with said master document; and sending data of said at least one second document to said output device separated from the data of said master document.

- 35.(Previously Presented) A method as claimed in claim 34, further comprising the step of: storing the data of said at least one second document in said output device.
- 36.(Previously Presented) A method as claimed in claim 34, further comprising the step of:
- joining the data of said master document with data of said at least one second document for output of an individual document.
- 37.(Previously Presented) A method as claimed in claim 34, wherein said step of logical linking ensues via a referencing.
- 38.(Previously Presented) A method as claimed in claim 34, further comprising the steps of:
- specifying an area of said master document wherein said at least one second document is to be linked with said master document.
- 39.(Previously Presented) A method as claimed in claim 37, wherein said area of said master document is a page region.
- 40.(Previously Presented) A method as claimed in claim 33, wherein said second document is one of an overlay and a watermark document.
- 41.(Currently Amended) A computer program product embodied on a computer readable media and operable to perform the steps of:
- generating a master document having a variable data area and having a static data area; marking said variable data area;
- inserting variable data into said variable data area to provide a serial data stream with individual documents, said individual documents respectively containing both variable data as well as static data;
- separating said variable data of said serial data stream from said static data on a basis of said marking;

- transmitting said variable data separated from said static data from a first individual document to the output device;
- storing said static data of said first individual document in said output device;
- said static data of following individual documents are not transmitted to said output device; and
- joining said variable data in turn with the stored static data individual document by individual document in said output device;
- said marking step of said variable data area ensues by a visually perceptible identification, said visually perceptible identification is a chromatic marking that is outside a printing range of a printer and which prints the variable data in a same color as a color of said static data.
- 42.(Currently Amended) A system for implementation of a method including at least one computer to perform a method for output of data from a computer system to an output device, including:
- generating a master document having a variable data area and having a static data area; marking said variable data area;
- inserting variable data into said variable data area to provide a serial data stream with individual documents, said individual documents respectively containing both variable data as well as static data;
- separating said variable data of said serial data stream from said static data on a basis of said marking;
- transmitting said variable data separated from said static data from a first individual document to the output device;
- storing said static data of said first individual document in said output device;
- said static data of following individual documents are not transmitted to said output device; and
- joining said variable data in turn with the stored static data individual document by individual document in said output device;
- said marking step of said variable data area ensues by a visually perceptible identification, said visually perceptible identification is a chromatic marking, said static data being printed by a printer in a color, said variable data being printed by the printer in the same color as said static data.